



<b>Customer</b>		<b>RoHS</b>	Yes
<b>Product Name</b>	Designated Power Distribution Unit for Cabinet	<b>Customer's Code</b>	
<b>Part Number</b>	AUE2230Y2-20AVFGMB	<b>Picture Code</b>	ITOL0321711015
<b>No.</b>	<b>Item</b>	<b>Detailed Description</b>	
1	Product Series	AUE2230	
2	Socket Type	Italy socket[20];	
3	Socket Quantity	20	
4	Power Input	Left end single input	
5	Bracket Install	Inverse installation	
6	Cable with plug	IEC60309 plug 32A 2P+E	
7	Control Function	32A Master air circuit breaker	
8	Protection Function	No protecting function	
9	Case	Black	
10	Cable Specification	3 x 6.0 mm <sup>2</sup> x 3M	
11	Product Size	L x W x H = 1228 x 68 x 44.4 mm	
12	Mounting Length	1207 mm	
13	Case Length	1175 mm	
14	PDU Exponent	21.951	
15	Fittings	2pcs $\phi$ 6×16mm cross bolt, 2pcs M6 float nut, PDU manual	
16	Product Label	Product Name	Designated Power Distribution Unit for Cabinet
		Specification Model	AUE2230Y2-20AVFGMB
		Rating voltage	250VAC 50/60Hz
		Rating Current	32A
		Max. Current	
		Max. Power	8000W
		Safety Authentication	CE
		Logo	CLEVER
Producer			
<b>No.</b>	<b>Add-In</b>		
1	Socket assemble	N/A	
2	Interior Connection Wire	4.0 mm <sup>2</sup> (12AWG)	
3	Interior Connection Style	Standard connection	
4	Fix the Cable	Cable clamp(19)	
5	Module Assemble ( from left to right )	Please refer to the drawing attached.	
6	Others	N/A	
<b>Made by:</b>		<b>Customer confirm:</b>	<b>Check:</b> <b>Authorize:</b>



Shenzhen Clever Electronic Co., Ltd – Lande Italy Srl



IEC60309 plug (32A 2P+E)

DIMENSION AND TOLERANCES (Unit: mm)			SHENZHEN CLEVER ELECTRONIC CO.,LTD	
Length: 1228	Mounting length: 1207		Customer	
Width: 68	Case length: 1175		Product name	Designated Power Distribution Unit for Cabinet
Height: 44.4	case tolerance: $\pm 1.0$		Part number	AUE2230Y2-20AVFGMB
	SIGN	DATE	Customer's code	
DRAWN			Drawing number	ITOL0321711015
CHK'D			Edition number	
APP'D				

PDU Technology Specification

NO.: ITOL0321711015