



<b>Customer</b>		<b>RoHS</b>	
		Yes	
<b>Product Name</b>		<b>Customer's Code</b>	
Designated Power Distribution Unit for Cabinet			
<b>Part Number</b>		<b>Picture Code</b>	
AUE2230H1-18HVNGMB		ITOT0321703002	
<b>No.</b>	<b>Item</b>	<b>Detailed Description</b>	
1	Product Series	AUE2230	
2	Socket Type	IEC320 C19 Socket(Single 2)[6];Double IEC320 C13 Socket[6];	
3	Socket Quantity	18	
4	Power Input	IEC320 C20 input	
5	Bracket Install	Inverse installation	
6	Cable with plug	No plug	
7	Control Function	16A Master air circuit breaker	
8	Protection Function	No protecting function	
9	Case	Black	
10	Cable Specification	N/A	
11	Product Size	L x W x H = 1046 x 68 x 44.4 mm	
12	Mounting Length	1025 mm	
13	Case Length	993 mm	
14	PDU Exponent	1. 305	
15	Fittings	2pcs $\phi 6 \times 16$ mm cross bolt, 2pcs M6 float nut, PDU manual	
16	Product Label	Product Name	Designated Power Distribution Unit for Cabinet
		Specification Model	AUE2230H1-18HVNGMB
		Rating voltage	250VAC 50/60Hz
		Rating Current	16A
		Max. Current	
		Max. Power	4000W
		Safety Authentication	CE
		Logo	CLEVER
	Producer		
<b>No.</b>	<b>Add-In</b>		
1	Socket assemble	N/A	
2	Interior Connection Wire	1.5 mm <sup>2</sup> (16AWG)	
3	Interior Connection Style	Standard connection	
4	Fix the Cable	N/A	
5	Module Assemble ( from left to right )	Please refer to the drawing attached.	
6	Others	N/A	
<b>Made by:</b>		<b>Customer confirm:</b>	<b>Check:</b> <b>Authorize:</b>



Preview



PDU Technology Specification

DIMENSION AND TOLERANCES ( Unit: mm )				
Length: 1046 Mounting length: 1025			Customer	
Width: 68 Case length: 993			Product name	
Height: 44.4 case tolerance: $\pm 1.0$			Designated Power Distribution Unit for Cabinet	
	SIGN	DATE	Part number	
			AUE2230H1-18HVNGMB	
DRAWN			Customer's code	
CHK'D			Drawing number	
			ITOT0321703002	
APP'D			Edition number	