



## PDU Technology Specification

<b>Customer</b>		<b>RoHS</b>	Yes
<b>Product Name</b>	Designated Power Distribution Unit for Cabinet	<b>Customer's Code</b>	
<b>Part Number</b>	AUE2250Y2-08AHDPMB	<b>Picture Code</b>	ITOL035160531003
<b>No.</b>	<b>Item</b>	<b>Detailed Description</b>	
1	Product Series	AUE2250	
2	Socket Type	Italy socket[8];	
3	Socket Quantity	8	
4	Power Input	Left end single input	
5	Bracket Install	Frontal installation	
6	Cable with plug	DIN49441 16A plug	
7	Control Function	Single power indicator	
8	Protection Function	No protecting function	
9	Case	Black	
10	Cable Specification	3 x 1.5 mm <sup>2</sup> x 2M	
11	Product Size	L x W x H = 486 x 44.4x 44.4 mm	
12	Mounting Length	459.5 mm	
13	Case Length	433 mm	
14	PDU Exponent	9. 026	
15	Fittings	2pcs $\phi$ 6×16mm cross bolt, 2pcs M6 float nut, PDU manual	
16	Product Label	Product Name	Designated Power Distribution Unit for Cabinet
		Specification Model	AUE2250Y2-08AHDPMB
		Rating voltage	250VAC 50/60Hz
		Rating Current	16A
		Max. Current	
		Max. Power	4000W
		Safety Authentication	CE
		Logo	RoHS
	Producer		
<b>No.</b>	<b>Add-In</b>		
1	Socket assemble	NO	
2	Interior Connection Wire	1.5 mm <sup>2</sup> (16AWG)	
3	Interior Connection Style	Standard connection	
4	Fix the Cable	Small cable clamp	
5	Module Assemble ( from left to right )	Pls refer to the drawing	
6	Others	NO	
<b>Made by:</b>		<b>Customer confirm:</b>	<b>Check:</b> <b>Authorize:</b>



DIN49441 16A plug

DIMENSION AND TOLERANCES ( Unit: mm )			SHENZHEN CLEVER ELECTRONIC CO.,LTD	
Length: 486	Mounting length: 459.5		Customer	
Width: 68	Case length: 433		Product name	Designated Power Distribution Unit for Cabinet
Height: 44.4	case tolerance: $\pm 1.0$		Part number	AUE2250Y2-08AHDPMB
	SIGN	DATE	Customer's code	
DRAWN		05/31/2016	Drawing number	ITol035160531003
CHK'D			Edition number	
APP'D				