



PDU Technology Specification

Customer		RoHS	Yes
Product Name	Designated Power Distribution Unit for Cabinet	Customer's Code	
Part Number	AUE2230E2-04LHFTMB	Picture Code	ITOT0321804005
No.	Item	Detailed Description	
1	Product Series	AUE2230上	
2	Socket Type	IEC320 C19 Socket(Single 2)[4];	
3	Socket Quantity	4	
4	Power Input	Back input	
5	Bracket Install	Frontal installation	
6	Cable with plug	IEC60309 plug (32A 2P+E)	
7	Control Function	4x 16A thermal breaker with LED	
8	Protection Function	No protecting function	
9	Case	Black	
10	Cable Specification	3 x 6.0 mm ² x 3M	
11	Product Size	L x W x H = 481.5 x 68 x 44.4 mm	
12	Mounting Length	460.5 mm	
13	Case Length	428.5 mm	
14	PDU Exponent	1. 113	
15	Fittings	2pcs ϕ 6×16mm cross bolt, 2pcs M6 float nut, PDU manual	
16	Product Label	Product Name	Designated Power Distribution Unit for Cabinet
		Specification Model	AUE2230E2-04LHFTMB
		Rating voltage	250VAC 50/60Hz
		Rating Current	32A
		Max. Current	
		Max. Power	8000W
		Safety Authentication	CE
		Logo	CLEVER
	Producer		
No.	Add-In		
1	Socket assemble	N/A	
2	Interior Connection Wire	4.0 mm ² (12AWG)	
3	Interior Connection Style	Standard connection	
4	Fix the Cable	Cable clamp(19)	
5	Module Assemble (from left to right)	Please refer to the drawing attached.	
6	Others	N/A	
Made by:		Customer confirm:	Check: Authorize:



Shenzhen Clever Electronic Co., Ltd – ITALAN S.r.l.



Preview



IEC60309 plug (32A 2P+E)

DIMENSION AND TOLERANCES (Unit: mm)			SHENZHEN CLEVER ELECTRONIC CO.,LTD	
Length: 481.5		Mounting length: 460.5		Customer
Width: 68		Case length: 428.5		Product name
Height: 44.4		case tolerance: ± 1.0		Part number
	SIGN	DATE	AUE2230E2-04LHFTMB	
DRAWN		08/27/2016	Customer's code	
CHK'D			Drawing number	ITOT0321804005
APP'D			Edition number	