





## NA054H3626 Specification

Customer			
Product Name	Factory Part No.	Customer Part No.	
NPM	NA054H3626		
Main Functions	Details		
Monitor	Total load current		
	Input Voltage		
	Total energy consumption (kWh)		
	Power Factor		
	Total power(kW)		
	Temperature and Humidity state ×4 port		
	Smoke state ×1 port		
	Door state ×2 port		
	Water logging ×1 port		
Control and configure	Set the threshold of total load current		
	Clear the total energy consumption(kWh)		
	Set the threshold of temperature and humidity		
	Set the work mode (master or slave)		
	Support external WIFI		
Alarm	User defined alarm	Set the threshold of total load current	
		Set the threshold of temperature and humidity	
	System default alarm	When overload occurs	
	Alarm method	LCD displays the alarm and buzzer sounds	
		Web interface show the value exceeded in red	
		Send E-mail to administrator automatically	
		SNMP sends trap alarm information	
		Logical port outputs level signal	
SYSLOGS			
Log record	Record and save the operating and alert information, graphic record of electric parameters and environment which can be exported.		
Daisy chain	Support Daisy-chain		
Central	Support central management of N units via CLEVER Manager software		
	Different user permission configuration		



User management	Outlet Alarm permission configuration					
	Set the permission to clear the energy consumption(kWh)					
Accessing method	Web based, support multiple browsers like IE, Google, Firefox etc.					
	SNMP (V1/V2C/V3)					
	Telnet					
	Serial Access (Modbus /RJ485)					
	RADIUS					
Input/output						
Input	Rated input voltage	250V~ 50/60 Hz				
	Input terminal type	IEC60309 2P+E 32A plug				
	Cable specification	3×6.0 mm <sup>2</sup> ;				
	Cable length	3M				
	The max input current	32A				
Output	Socket	IEC320 C13	Rated current	10A	Outlet	30
	Socket	IEC320 C19	Rated current	16A	Outlet	6
	Rated output voltage	250VAC				
Dimension	Product size	L×W×H = 1770×66.6×44.4mm (including brackets)				
Special requirement: single pole 32A RCCB (30mA leakage protection)						
PDU overview:						
						
						
IEC60309 plug (32A)						
Design: Maple	Customer confirm:	Check:	Authorized:			