





ND054H1626 Specification

Customer	Out Line S.R.L	
Product Name	Factory Part No.	Customer Part No.
NPM	ND054H1626	
Main Functions	Details	
Monitor	Total load current	
	Outlet load current	
	Input Voltage	
	Total energy consumption (kWh)	
	Outlet energy consumption (kWh)	
	Power Factor	
	Total power(kW and kVA)	
	Outlet power (kW)	
	Environmental status such as Temperature/Humidity/Smoke/Water logging/Door	
	On/Off state of each outlet	
Control and configure	Switch on/off individual outlet	
	Set the threshold of total load current	
	Set the threshold of individual load current	
	Set the delay of outlet sequential switching	
	Clear the total energy consumption(kWh)	
	Clear the outlet energy consumption (kWh)	
	Set the threshold of temperature and humidity	
	Set the work mode (master or slave)	
Support external WIFI		
Keep the former state	Keep the former state of individual outlet after reset	
Alarm	User defined alarm	Set the threshold of total load current
		Set the threshold of outlet load current
		Set the threshold of temperature and humidity
	System default alarm	When overload occurs
		When Threshold of outlet load current is exceeded
		When Threshold of temperature and humidity is exceeded
	Alarm method	LCD displays the alarm and buzzer sounds
		Web interface show the value exceeded in red
		Send E-mail to administrator automatically
		SNMP sends trap alarm information



		Logical port outputs level signal				
		SYSLOGS				
Log record	Record and save the operating and alert information, graphic record of electric parameters and environment which can be exported.					
Daisy chain	Support Daisy-chain					
Central	Support central management of N units via CLEVER Manager software					
User management	Different user permission configuration					
	Outlet Alarm permission configuration					
	Set the permission to clear the energy consumption(kWh)					
Accessing method	Web based, support multiple browsers like IE, Google, Firefox etc.					
	SNMP (V1/V2C/V3)					
	Telnet					
	Serial Access					
	RADIUS/SMTP/DHCP/TCP/IP /NTP					
Input/output						
Input	Rated input voltage	250V~ 50/60 Hz				
	Input terminal type	IEC60309 2P+E 32A plug				
	Cable specification	3×6.0mm ² ;				
	Cable length	3M				
	The max input current	32 A				
Output	Socket	IEC320 C13	Rated current	10A	Outlet	8
	Socket	DIN49440 Schuko	Rated current	16A	Outlet	8
	Rated output voltage	250VAC				
Dimension	Product size	L×W×H =1750×66.6×44.4mm				
PDU overview						
						
						
IEC60309 32A 2P+E plug						
Design: Maple	Customer confirm:		Check:		Authorized:	